

QUALITY INKJET PRINTING

IJ3160

INKJET VALIDATION PRINTER

Addmaster's IJ3160 validates up to eight lines of 42 characters each on various forms and documents. The IJ3160 may be used to validate forms commonly used in bank teller systems, payment processing, cash settlement and other applications. Media may include checks, cut-forms such as deposit slips and cash tickets, envelopes, labels or cards. For faster form handling, the printer's validation slot always stays open ready to receive the form.

The IJ3160 prints at a quiet 49 decibels using the trouble-free Hewlett-Packard inkjet cartridge. The inkjet cartridge is a non-impact print head without moving parts. This long-lasting cartridge is easily inserted and is simply discarded and replaced when the ink is expended. The IJ3160 eliminates the hassle and mess associated with impact printers and ribbons. Reliability is increased over impact printers due to the absence of moving parts on the print head and an advanced state-of-the-art design with fewer mechanical and electrical components.

The IJ3160 is an excellent alternative to impact printers and its quiet printing is ideal for bank lobbies, and other environments where noise levels are of concern.

With a compact footprint of only 39 square inches (6" x 6.5"), the IJ3160 takes up very little space.



- QUIET
- COMPACT
- USER-FRIENDLY
- TROUBLE-FREE
- ENERGY-EFFICIENT

 **ADDMASTER**
The Inkjet Authority

INKJET VALIDATION PRINTER
IJ3160

Print Method: Thermal Inkjet Cartridge • HP51604A

Print Characteristics: Character Set: 96 character ASCII set • Character Height: 0.125"

Validation Characteristics: Horizontal Field: 2.8" • 42 characters at 15 characters per inch
Top Line: 1.5" (from bottom of form) • Number of Lines: 8
Line Spacing: 6.6 lines per inch

Font & Pitch: Standard or Large • Regular or Bold • Single or Double
5 to 15 characters per inch

Interface: RS232 • Parallel

Dip Switch Selections: Baud Rate: 1,200 • 9,600 Parity: Even • Odd • None
Data Bits: 7 or 8 • 1 stop bit

Available Emulations: NCR 2567 • IBM 4712 / 4770 • Olivetti PR46S • DH4411

Dimensions: Width: 6.5" • Depth: 6" • Height: 3.4"

Weight: 2.4 lbs.

Shipping Weight: With Accessories: 5.2 lbs. • Without Accessories: 3.4 lbs.

Operator Controls: Power Switch • Two LED Status Indicators

Power Source: 12 - 14 Volt DC @ 500ma

Power Consumption: Operating: 8 watts • Standby: 1 watt

Operating Environment: 10 degrees to 40 degrees C • 10% to 90% RH (non-condensing)

Sound Level: 49 Decibels at 24 inches

Options: 8k Buffer • Graphics • Form Rack

Complete Code Page 437 (English)

Complete Code Page 850 (Multi-Lingual)



ADDMASTER CORPORATION • WWW.ADDMASTER.COM
P.O. Box 5016, Monrovia, CA 91017-7116 • T 626-358-2395 • F 626-358-2784

© 2003 Addmaster Corporation. Specifications subject to change without notice.